

08004

kućište za zidnu montažu 4 reda Prisma Pack 160
IP30



Glavno

| | |
|------------------------------------|--|
| Range | Prisma |
| Product name | Pack 160 |
| IP degree of protection | IP31 with door and canopy IP43 with door, canopy and IP43 gasket IP30 with door IP30 without door |
| Product or component type | Enclosure |
| Enclosure type | Modular enclosure |
| Enclosure mounting | Surface Flush with kit |
| Type of front cover | Modular |
| Number of vertical modules [50 mm] | 12 |
| Number of 18 mm modules per row | 24 |
| Provided equipment | Enclosure (x1) Earthing kit (x1) Front plate (x4) Modular rail (x4) |

Komplementarno

| | |
|--|--|
| Enclosure/cubicle description | Pack enclosure - width 555 mm |
| [Ui] rated insulation voltage | 750 V on main rear busbars conforming to IEC 61439-2 |
| [In] rated current | 160 Aat 40 °C conforming to IEC 61439-2 |
| [Icw] rated short-time withstand current | 25 kA (1 s) conforming to IEC 61439-2 |
| [Ipk] rated peak withstand current | 53 kA conforming to IEC 61439-2 |
| Network frequency | 50/60 Hz |
| Number of horizontal rows | 4 |
| Enclosure material | Enclosure: treated sheet steel |
| Quantity per set | Set of 1 |
| Height | 780 mm |
| Width | 555 mm |
| Depth | 157 mm |
| Product weight | 12.84 kg |
| Surface finish | Matt Smooth |
| Colour | White RAL 9001 |

Okolina

| | |
|-------------------------|--|
| IK degree of protection | IK08 with door IK07 without door conforming to EN/IEC 62262 |
| protective treatment | Electrophoresis treatment and hot-polymerised polyester epoxy powder |
| standards | IEC 62208 IEC 61439-2 IEC 61439-1 IEC 61439-3 |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 1809 - Schneider Electric declaration of conformity | Compliant - since 1809 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Need no specific recycling operations | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|