



Glavno

Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for power outlet
Accessories included with enclosure	2 plates for push-button controls 2 wiring straps 8 plates for 65 x 85 power outlets

Komplementarno

Enclosure mounting	Surface
Number of 18 mm modules per row	18
Total number of 18 mm modules	19
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	8
Number of plates	8for 65 x 85 power outlets 2for push-button controls
Provided equipment	2 wiring strap 8 plate for 65 x 85 power outlet 2 plate for push-button control
Type of front cover	Transparent
Power dissipation in W	39 W
[In] rated current	90 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 16 outgoers
Locking options description	Optional keylock
Enclosure material	Housing: self-extinguishing polymer
Product weight	3.4 kg
Base dimension	90 x 100 mm
Width	448 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)

Okolina

standards	EN 50262 EN 62262 IEC 60439-3 IEC 60529 IEC 60695-2-1 IEC 670
fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102

Informacije dane u ovoj dokumentaciji sadrže opće opisne i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu sadržanih informacija.

environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
overvoltage category	II
ambient air temperature for operation	-25...40 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------