

Podatkovni list proizvoda

Karakteristike

13191

Kaedra – višenamjenski za strujne utičnice – 1 x 12+1 modula – 340 x 335 mm



Glavno

Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Versatile enclosure for power outlet

Komplementarno

Enclosure mounting	Surface
Number of 18 mm modules per row	12
Total number of 18 mm modules	12
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Type of front cover	Transparent
Power dissipation in W	23 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Locking options description	Optional keylock
Enclosure material	Housing: self-extinguishing polymer
Product weight	2 kg
Width	340 mm
Height	335 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)

Okolina

standards	EN 50262 EN 62262 IEC 60439-3 IEC 60529 IEC 60695-2-1 IEC 670
fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
overvoltage category	II
ambient air temperature for operation	-25...40 °C

Contractual warranty

