

Podatkovni list proizvoda

Karakteristike

13192

Kaedra – višenamjenski za strujne utičnice – 1 x 12+1 modula – 340 x 460 mm



Glavno

| | |
|---------------------------|--------------------------------------|
| Range | Kaedra |
| Product or component type | Weatherproof enclosure |
| Enclosure type | Versatile enclosure for power outlet |

Komplementarno

| | |
|---------------------------------|---|
| Enclosure mounting | Surface |
| Number of 18 mm modules per row | 12 |
| Total number of 18 mm modules | 12 |
| Number of horizontal rows | 1 |
| Electrical insulation class | Class II Double insulation |
| Type of front cover | Transparent |
| Power dissipation in W | 28 W |
| [In] rated current | 90 A |
| Type of rail | DIN |
| Number of pre-cutouts PG ISO | 17 |
| Locking options description | Optional keylock |
| Enclosure material | Housing: self-extinguishing polymer |
| Product weight | 2.8 kg |
| Width | 340 mm |
| Height | 460 mm |
| Depth | 160 mm |
| Colour | Door : transparent green Enclosure : light grey (RAL 7035) |

Okolina

| | |
|---------------------------------------|--|
| standards | EN 50262 EN 62262 IEC 60439-3 IEC 60529 IEC 60695-2-1 IEC 670 |
| fire resistance | 650 °C conforming to IEC 60695-2-1 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK09 conforming to EN 50102 |
| environmental characteristic | UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013 |
| overvoltage category | II |
| ambient air temperature for operation | -25...40 °C |

Contractual warranty

