



### Glavno

Range of product	Acti 9
Range	Acti 9
Product name	Acti 9 iCM
Product or component type	Selector switch
Device short name	ICMV
Device application	Voltmeter selector
[Ue] rated operational voltage	< 440 V AC 50/60 Hz

### Komplementarno

[Ith] conventional free air thermal current	10 A
[Ie] rated operational current	10 A
Control type	Rotary handle 7 positions
Marking	L3L1 - L2L3 - L1L2 - 0 - L1N - L2N - L3N
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	60 mm
Width	36 mm
Depth	75 mm
Mechanical durability	2000000 cycles
Electrical durability	1000000 cycles
Connections - terminals	Captive screw-jumper terminals

### Okolina

standards	IEC 60947-3
IP degree of protection	IP66 front face IP20 terminals
ambient air temperature for operation	-20...55 °C
ambient air temperature for storage	-25...80 °C

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0705 - Schneider Electric declaration of conformity	Compliant - since 0705 - Schneider Electric declaration of conformity

### Contractual warranty

Warranty period	18 months
-----------------	-----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i popunivu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.