



### Glavno

Range	Acti 9
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[Ie] rated operational current	1 A at 130 V DC 2 A at <= 48 V DC 3 A at >= 240 V AC 6 A at < 240 V AC 6 A at <= 24 V AC
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC
9 mm pitches	4
Product compatibility	NG125

### Komplementarno

Range compatibility	Acti 9 Vigii NG125 Acti 9: Acti 9 NG125LMA Acti 9: Acti 9 NG125NA Acti 9: Acti 9 NG125
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-5-1
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	105 mm
Width	32 mm
Depth	78 mm
Product weight	0.132 kg
Electrical durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - terminals	Plate terminal 2 cable(s) 2.5 mm <sup>2</sup> flexible Plate terminal 2 cable(s) 2.5 mm <sup>2</sup> rigid Plate terminal 1 cable(s) 0.5...2.5 mm <sup>2</sup> rigid Plate terminal 1 cable(s) 0.5...1.5 mm <sup>2</sup> flexible Plate terminal 1 cable(s) 0.5...1.5 mm <sup>2</sup> flexible with ferrule Plate terminal 2 cable(s) 1.5 mm <sup>2</sup> flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

### Okolina

standards	EN/IEC 60947-5-1
product certifications	EAC
IP degree of protection	IP20 B conforming to EN/IEC 60947-5-1 IP4 conforming to EN/IEC 60947-5-1
pollution degree	3 conforming to EN/IEC 60947-5-1
overvoltage category	II
tropicalisation	2 conforming to EN/IEC 60947-5-1
relative humidity	95 % at 55 °C
ambient air temperature for operation	-25...60 °C
ambient air temperature for storage	-40...85 °C

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---