

## AK5JB144

sabirnica 160 A – duljina 452 mm – za AK5



### Glavno

Range	Linergy
Product name	HK
Product or component type	Busbar
Device application	Distribution
Number of tap-offs	18
Bar length	452 mm
Enclosure/cubicle width	800 mm
Network type	AC
[Ie] rated operational current	160 A at 35 °C
[Ue] rated operational voltage	400 V (off-load plugging-in and unplugging, with supply switched on) conforming to IEC 60439-1 480 V (off-load plugging-in and unplugging, with supply switched on) conforming to CSA 480 V (off-load plugging-in and unplugging, with supply switched on) conforming to UL 600 V (plugging-in and unplugging, with supply switched off) conforming to CSA 600 V (plugging-in and unplugging, with supply switched off) conforming to UL 690 V (plugging-in and unplugging, with supply switched off) conforming to IEC 60439-1
Number of conductors	4

### Komplementarno

Bar width	40 mm
Width	80 mm
Depth	84 mm
Network frequency	50/60 Hz
[Ui] rated insulation voltage	600 V conforming to UL 690 V conforming to IEC 60439-1 600 V conforming to CSA
Peak current	25 kA
I <sup>2</sup> t on activation	10000000 A <sup>2</sup> .s
Protection type	AM fuses (In = 160 A, I <sub>sc</sub> = 100 kA, I <sub>e</sub> = 160 A) GF fuses (In = 160 A, I <sub>sc</sub> = 100 kA, I <sub>e</sub> = 160 A) NS160H circuit breaker (In = 160 A, I <sub>sc</sub> = 36 kA, I <sub>e</sub> = 160 A) NS160H circuit breaker (In = 160 A, I <sub>sc</sub> = 70 kA, I <sub>e</sub> = 160 A)
Connections - terminals	Connector, 2.5...70 mm <sup>2</sup> flexible cable with cable end Connector, 2.5...70 mm <sup>2</sup> rigid cable
Tightening torque	10 N.m
Mounting position	Horizontal mounting Vertical mounting using side stop AK5BT01 on mounting plates AK5PA
Flame retardance	V0 conforming to UL 94
Product weight	0.9 kg

### Okolina

standards	IEC 60439
product certifications	CSA DNV LROS (Lloyds register of shipping) UL
IP degree of protection	IPxx B conforming to IEC 60529
fire resistance	850 °C conforming to IEC 60695

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0713 - Schneider Electric declaration of conformity	Compliant - since 0713 - Schneider Electric declaration of conformity
Available	Available
Need no specific recycling operations	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------