

CCT15233

Acti 9–MINp–tihi elektronički brojač–mogućnost podešavanja od 0,5 do 60 minuta



Glavno

Range	Acti 9
Product name	Acti 9 MIN
Device short name	MINp
Product or component type	Silent electronic timer
Product compatibility	Mechanical compatibility with electrical comb busbars
Function available	Switch-off warning
Colour tint	White (RAL 9003)

Komplementarno

Device application	Building
Load type	22 fluorescent lamp, balast : electronic, (23 W) 230 V AC halogen lamp, (3600 W) 230 V AC incandescent lamp, (3600 W) 24 fluorescent lamp, balast : electronic, (15 W) 27 fluorescent lamp, balast : electronic, (11 W) 34 fluorescent lamp, balast : electronic, (7 W) Dual mounted fluorescent tube, balast : conventional, (3600 VA) Fluocompact lamp, balast : conventional, (1500 VA) Fluorescent tube, balast : electronic, (1000 VA) Non-corrected fluorescent tube, balast : conventional, (3600 VA) Parallel-corrected fluorescent tube, balast : conventional, (1200 VA) Serial-corrected fluorescent tube, balast : conventional, (3600 VA)
Power consumption in VA	<= 6 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V (+10 % -15 %) AC 50/60 Hz
Time delay	Adjustable from 0.5 to 60 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals
Electrical insulation class	Class II
Width	18 mm
Height	89 mm
Depth	66 mm
Product weight	103 g

Okolina

ambient air temperature for operation	-25...50 °C
IP degree of protection	IP20 B

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1346 - Schneider Electric declaration of conformity	Compliant - since 1346 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period	18 months
-----------------	-----------
