

LA4DT0U

modul za elektronički brojač – vrsta s odgodom
0,1...2 s – 24...250 V DC/AC



Glavno

Range	TeSys
Product or component type	Serial timer modules
Device short name	LA4DT
Poles description	3P
Product compatibility	LC1D09...D65A LC1D80...D150

Komplementarno

Mounting location	Top
[Uc] control circuit voltage	24...250 V AC 50/60 Hz 24...250 V DC
Control circuit voltage limits	0.8...1.1 Uc by mechanical contact
[Ui] rated insulation voltage	250 V - conforming to IEC 60947-1
Connections - terminals	Control circuit: connector 1 cable 1 mm ² - cable stiffness: flexible - with cable end Control circuit: connector 1 cable 1 mm ² - cable stiffness: solid - with cable end Control circuit: connector 2 cable 2.5 mm ² - cable stiffness: flexible - without cable end Control circuit: connector 2 cable 2.5 mm ² - cable stiffness: solid - without cable end
Electrical durability	30 Mcycles
Timer type	On delay
Time delay range	0.1...2 s
Reset time	150 ms during time delay 50 ms after time delay
Local signalling	Illuminates during time delay by LED
[Ures] residual voltage	3.3 V
Product weight	0.04 kg

Okolina

standards	IEC 60255-5
product certifications	CSA UL
IP degree of protection	IP2x conforming to VDE 0106
protective treatment	TH conforming to IEC 60068
ambient air temperature for operation	-25...55 °C
permissible ambient air temperature around the device	-25...70 °C
ambient air temperature for storage	-40...80 °C
protection type	Built-in by varistor
heat dissipation	2 W at 50/60 Hz
immunity to microbreaks	10 ms during time delay 2 ms after time delay

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0850 - Schneider Electric declaration of conformity	Compliant - since 0850 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
 Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešku upotrebu ovdje sadržanih informacija.

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
