

**Podatkovni list proizvoda**  
**Karakteristike**

**LC1E40B7****Glavno**

Range	EasyPact
Product name	EasyPact TVS
Product or component type	Contactor
Device short name	LC1E
Contactor application	Motor control Resistive load
Utilisation category	AC-1 AC-3
Poles description	3P
Pole contact composition	3 NO
[Ue] rated operational voltage	<= 690 V AC 50/60 Hz for power circuit
[Ie] rated operational current	40 A (<= 60 °C) AC AC-3 for power circuit <= 440 V 60 A (<= 60 °C) AC AC-1 for power circuit <= 440 V
Motor power kW	11 kW at 220...230 V AC 50/60 Hz 22 kW at 415 V 22 kW at 440 V 18.5 kW at 380...400 V 22 kW at 500 V 30 kW at 660...690 V
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	24 V AC 50/60 Hz
Height	127 mm
Width	75 mm
Depth	114 mm
Product weight	0.98 kg
Colour	Grey RAL 7011

**Komplementarno**

Auxiliary contact composition	1 NO + 1 NC
[Uimp] rated impulse withstand voltage	6 kV (coil not connected to the power circuit) IEC 60947
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III
Irms rated making capacity	400 A - 440 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	320 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	320 A at <= 40 °C - 10 s for power circuit 165 A at <= 40 °C - 60 s for power circuit 72 A at <= 40 °C - 600 s for power circuit
Associated fuse rating	80 A gG <= 690 V type 1 power circuit 10 A gG <= 690 V type 1 control circuit IEC 60947-5-1
Average impedance	1.5 mOhm at 50 Hz Ith 60 A for power circuit
Power dissipation per pole	5.4 W AC-1 2.4 W AC-3
Control circuit voltage limits	0.85...1.1 Uc at <= 55 °C operational 50/60 Hz 0.3...0.6 Uc at <= 55 °C drop-out 50/60 Hz
Operating time	20...26 ms on closing 8...12 ms on opening
Mechanical durability	5000000 cycles
Operating rate	1200 cyc/h at <= 55 °C
Inrush power in VA	160 VA at 20 °C (0.75) 50 Hz 140 VA at 20 °C (0.75) 60 Hz

Informacije dane u ovom dokumentu sadrže opće ili tehničke karakteristike o performansama ovde sadržanih proizvoda. Ova dokumentacija nije namijenjena za niti bi se trebala koristiti za određivanje prilidnosti ili pouzdanosti predmetnih proizvoda za konkrete korisničke primjene. Svaki takav korisnik ili integrator duž je provesti potpunu analizu rizika, prijenos i spajanje proizvoda u odnos na odgovarajuću specifičnu primjenu ili uporabu istog. Niti državno Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili snositi odgovornost za pogresnu upotrebu ovde sadržanih informacija.

Hold-in power consumption in VA	13 VA at 20 °C (0.3) 60 Hz 15 VA at 20 °C (0.3) 50 Hz
Heat dissipation	6...10 W for control circuit
Minimum switching current	5 mA control circuit
Minimum switching voltage	17 V control circuit
Non-overlap time	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
Insulation resistance	> 10 MΩ control circuit
Electrical durability	350000 cycles AC-1 900000 cycles AC-3
Mounting support	DIN rail Plate
Connections - terminals	Control circuit: screw clamp terminals - 1 flexible cable(s) 1...4 mm² without cable end Control circuit: screw clamp terminals - 2 flexible cable(s) 1...4 mm² without cable end Control circuit: screw clamp terminals - 1 flexible cable(s) 1...4 mm² with cable end Control circuit: screw clamp terminals - 2 flexible cable(s) 1...2.5 mm² with cable end Control circuit: screw clamp terminals - 1 solid cable(s) 1...4 mm² without cable end Control circuit: screw clamp terminals - 2 solid cable(s) 1...4 mm² without cable end Power circuit: screw clamp terminals - 1 flexible cable(s) 2.5...25 mm² with cable end Power circuit: screw clamp terminals - 2 flexible cable(s) 2.5...10 mm² with cable end Power circuit: screw clamp terminals - 1 solid cable(s) 2.5...25 mm² without cable end Power circuit: screw clamp terminals - 2 solid cable(s) 2.5...16 mm² without cable end
Tightening torque	1.2 N.m for control circuit 5 N.m for power circuit

## Okolina

standards	IEC 60947-1 IEC 60947-4-1 IEC 60947-5-1
product certifications	EAC
IP degree of protection	IP2x conforming to IEC 60529
protective treatment	TH IEC 60068 3
pollution degree	3
ambient air temperature for operation	-5...55 °C
ambient air temperature for storage	-60...80 °C
permissible ambient air temperature around the device	-20...70 °C at Uc
operating altitude	3000 m without derating
fire resistance	850 °C IEC 60695-2-1
mechanical robustness	Vibrations contactor closed 3 Gn, 5...300 Hz Shocks contactor open 6 Gn for 11 ms Vibrations contactor open 1.5 Gn, 5...300 Hz Shocks contactor closed 7 Gn for 11 ms

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1350 - Schneider Electric declaration of conformity	Compliant - since 1350 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations