



Glavno

Range of product	NSX100...250 NSX100...250 DC
Product or component type	Trip unit
Range compatibility	Compact NSX100 Compact NSX160 Compact NSX250 Compact NSX100 DC Compact NSX160 DC Compact NSX250 DC
Device application	Distribution
Poles description	3P
Protected poles description	3t
Network type	AC
Network frequency	50/60 Hz
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Trip unit rating	25 A 40 °C
Protection type	Overload protection (thermal) L Short-circuit protection (magnetic) I

Komplementarno

Mounting mode	Fixed
[Ue] rated operational voltage	690 V AC 50/60 Hz
Long time pick-up adjustment type Ir	Adjustable
Long time pick-up adjustment range	0.7...1 x In
Long time delay adjustment type	Fixed
[tr] long-time delay adjustment range	120...400 s at 1.5 x In 15 s at 6 x Ir
Short-time pick-up adjustment type Isd	Fixed
[Isd] short-time pick-up adjustment range	300
Short-time delay adjustment type	Fixed

Okolina

standards	EN/IEC 60947-2 UL 508
product certifications	CCC Marine EAC
IP degree of protection	IP40 conforming to IEC 60529
pollution degree	3 conforming to IEC 60947-1
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0819 - Schneider Electric declaration of conformity	Compliant - since 0819 - Schneider Electric declaration of conformity

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------