



### Glavno

Range of product	EasyPact CVS400...630
Range	EasyPact
Product name	EasyPact CVS
Device short name	CVS400NA
Product or component type	Switch disconnecter
Device application	Distribution
Poles description	4P
Network type	AC
[Ie] rated operational current	400 A AC-22A: AC 50/60 Hz 220/240 V 400 A AC-22A: AC 50/60 Hz 440 V 400 A AC-23A: AC 50/60 Hz 220/240 V 400 A AC-23A: AC 50/60 Hz 440 V 400 A AC-22A: AC 50/60 Hz 380/415 V 400 A AC-23A: AC 50/60 Hz 380/415 V
[Ith] conventional free air thermal current	400 A ( 50 °C )
[Icm] rated short-circuit making capacity	105 kA with upstream protection circuit breaker 7.1 kA switch-disconnector alone
Breaking capacity code	NA
Suitability for isolation	Yes conforming to EN 60947-3 Yes conforming to IEC 60947-3
Utilisation category	AC-22A AC-23A
Earth-leakage protection	Without

### Komplementarno

Network frequency	50/60 Hz
Control type	Toggle
Mounting mode	Fixed
Mounting support	Backplate
Upside connection	Front
Downside connection	Front
[Icw] rated short-time withstand current	1.93 kA ( 20 s ) conforming to IEC 60947-3 5 kA ( 1 s ) conforming to IEC 60947-3 5 kA ( 3 s ) conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Mechanical durability	15000 cycles conforming to IEC 60947-3
Electrical durability	4000 cycles conforming to IEC 60947-3 415 V In AC 50/60 Hz AC-22A: 4000 cycles conforming to IEC 60947-3 415 V In AC 50/60 Hz AC-23A:
Connection pitch	45 mm
Height	255 mm
Width	185 mm
Depth	110 mm
Product weight	7.9 kg

### Okolina

standards	EN 60947-3 IEC 60947-3
-----------	---------------------------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

product certifications	GOST IEC
electrical shock protection class	Class II
pollution degree	3 conforming to IEC 60664-1
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1041 - Schneider Electric declaration of conformity	Compliant - since 1041 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available