



Glavno

Range	Spacial
Accessory / separate part category	Support accessory
Product or component type	Bar support
Device application	Multi-purpose Prisma application
Enclosure nominal dimensions	
Mounting location	Bottom
Busbar position	Vertical
Range compatibility	Spacial SFP Prisma PH Linergy LGYE Linergy BS Spacial SFM

Komplementarno

Cubicle-device connection	Linergy BS lateral busbar Linergy LGYE lateral busbar
Device composition	1 insulating bar support Fixing elements 1 metal support
Quantity per set	Set of 1
Material	Steel for metal support Plastic for bar support
Fixing mode	By fixing element - bottom frame of enclosure location
Height	66 mm
Width	Nominal: 800 mm Fixing centers: 750 mm
Depth	39 mm

Okolina

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0940 - Schneider Electric declaration of conformity	Compliant - since 0940 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.