

## NSYCCOTHI

ClimaSys CC – termostat od 250 V – raspon temperature +5... 60 °C – 1 NO/NC – °C



### Glavno

Range	ClimaSys
Product name	ClimaSys CC
Product or component type	Termostat
Temperature setting range	5...60 °C
Information displayed	Temperature in °C

### Komplementarno

Input voltage	250 V
Sensor type	Bimetal
Contacts type and composition	1 NO/NC
Contact resistance	< 10 mOhm
Service life in cycles	>= 100000 cycles
Maximum switching capacity	30 W DC 10 A 250 V AC inductive 4 A 250 V AC inductive pf: 0.6
Electrical connection	4 terminals 2.5 mm <sup>2</sup>
Mounting mode	Clipped
Height	External: 68 mm
Width	External: 56 mm
Depth	External: 44 mm
Product weight	100 g
Mounting location	On mounting plate 35 mm DIN rail Spacial upright Cross rails
Ambient air temperature for operation	-20...80 °C
IP degree of protection	IP20
Hysteresis	7 %
Number of outputs	1 output(s) heating function 1 output(s) ventilation function
Material	PC
Colour	Light grey
Flame retardance	Self-extinguishing conforming to UL94 (material V0)
Product certifications	UL

### Okolina

#### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0940 - Schneider Electric declaration of conformity	Compliant - since 0940 - Schneider Electric declaration of conformity

#### Contractual warranty

Warranty period	18 months
-----------------	-----------

