

## NSYCRN65150T

Spacial CRN prozir. vrata bez mont. ploče V600 x  
S500 x D150 IP66 IK08 RAL7035.



### Glavno

|                             |   |
|-----------------------------|---|
| Range                       | Spacial   |
| Product name                | Spacial CRN                                       |
| Device application          | Multi-purpose                                     |
| Product or component type   | Compact enclosure                                 |
| Enclosure nominal height    | 600 mm  |
| Enclosure nominal width     | 500 mm  |
| Enclosure nominal depth     | 150 mm  |
| Installation accessory type | Wall-mounting                                     |
| Device composition          | Lock 1<br>Door 1<br>Body 1<br>Cable gland plate 1 |
| Door type                   | Glazed  |
| Mounting plate description  | Without mounting plate                            |

### Komplementarno

|                             |  |
|-----------------------------|--|
| Variant particularity       | Sides made from a single folded section<br>Back welded with double profile forming a protected sealed area |
| Number of doors             | 1 front face   |
| Door opening side           | Reversible 120 °   |
| Lock type                   | 3 mm double-bar lock   |
| Type of gland plate         | Standard   |
| Accessibility for operation | Front  |
| Removable parts             | Door by hinges<br>Cable gland plate by screws  |
| Material                    | Steel for body<br>Steel and security glass for door  |
| Surface finish              | Epoxy-polyester powder   |
| Colour                      | Grey RAL 7035  |
| Standards                   | IEC 62208  |
| Product certifications      | CUL<br>UL  |
| Product weight              | 10.328 kg  |

### Okolina

|                         |                              |
|-------------------------|------------------------------|
| IP degree of protection | IP66 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to IEC 62262 |

### Offer Sustainability

|   |   |
|---|---|
| Green Premium product   | Green Premium product   |
| Compliant - since 0810 - Schneider Electric declaration of conformity | Compliant - since 0810 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold                     | Reference not containing SVHC above the threshold                     |
| Available   | Available   |
| Need no specific recycling operations                                 | Need no specific recycling operations                                 |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period

18 months