



### Glavno

Range	Thalassa
Product name	Thalassa PLS
Device short name	PLS
Device application	Multi-purpose
Product or component type	Insulating modular rear
Enclosure nominal height	360 mm
Enclosure nominal width	360 mm
Enclosure nominal depth	135 mm
Enclosure mounting	Wall mounted
Device composition	Rear part 1 on enclosure
Body type	One piece moulded
Type of front cover	Without

### Komplementarno

Material	Polyester reinforced with fibreglass
Colour	Grey RAL 7035 body
Standards	NEMA 4X IEC 62208 NEMA classification 13
Product certifications	UL

### Okolina

electrical insulation class	Class II
IP degree of protection	IP65 IEC 60529
IK degree of protection	IK09 IEC 62262
fire resistance	960 °C IEC 62208
ambient air temperature for storage	-30...70 °C

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1511 - Schneider Electric declaration of conformity	Compliant - since 1511 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.