



### Glavno

Range	Thalassa
Product name	Thalassa PHD
Product specific application	Outdoor heavy duty
Product certifications	UL conforming to UL 508 A (2007) Bureau Veritas conforming to IEC 61969-3 (2011) Bureau Veritas conforming to IEC 61439-5 (2010) DEKRA conforming to IEC 62208 (2011)
Device application	Multi-purpose
Product or component type	Suitable enclosure
Device short name	PHDZT
Enclosure nominal height	788 mm
Height	38 mm
Enclosure nominal width	500 mm
Enclosure nominal depth	320 mm
Enclosure mounting	Wall mounted
Device composition	1 body in polyester double reinforced with fibreglass 1 door in polyester double reinforced with fibreglass 1 canopy in polyester double reinforced with fibreglass 1 door retainer in steel with anti-corrosive coating 1 document pocket in plastic A4 format

### Komplementarno

Body type	Sealed assembled body
Door type	Plain
Number of doors	1
Door opening side	120 °
Lock type	2 points lock, handle with 1242E key lock and padlock
Accessibility for operation	Front
Maximum load	180 kg
Removable parts	Door by hinges
Material	Polyester double reinforced with fibreglass
Colour	Grey RAL 7035
Standards	IEC 62208 UL 508 A IEC 61969-3 IEC 61439-5
Electrical insulation class	Class II IEC 61439-1 2011

### Okolina

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK10 plain door conforming to IEC 62262
mechanical robustness	Vandal-proof conforming to EN/IEC 61439-5
fire resistance	960 °C IEC 62208
ambient air temperature for operation	-45...80 °C conforming to IEC 61969-3 class 1
ambient air temperature for storage	-25...40 °C
relative humidity	C4H level conforming to ISO 12944

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

environmental characteristic	Solar radiation: class 1 up to 1120 W/m <sup>2</sup> conforming to IEC 61969-3 (2011) Surrounding air withstand: class 1 up to 180 km/h conforming to IEC 61969-3 (2011) Ultraviolet degradation test: class 1 conforming to ISO 4892-2 (2013) Formation of ice and frost: class 1 conforming to IEC 61969-3 (2011) Fauna and flora withstand: class 1 conforming to IEC 61969-3 (2011) Chemical substance: class 1 conforming to IEC 61969-3 (2011)
power dissipation in W	Natural : Potential heat dissipation : 372 W at -25 °C Natural : Potential heat dissipation : 163 W at 20 °C Natural : Potential heat dissipation : 69 W at 40 °C Fan: Potential heat dissipation : 1500 W for a maximum noise level of 60 dB

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0940 - Schneider Electric declaration of conformity	Compliant - since 0940 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available