

NSYS3X4320T

Kućište od nehr.čelika SPACIAL S3X 304L, Scotch Brite® premaz, V400xŠ300xD200mm.



Glavno

Range	Spacial
Product name	Spacial S3X
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	400 mm
Enclosure nominal width	300 mm
Enclosure nominal depth	200 mm
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 1 lock (door)

Komplementarno

Body type	Single piece body, cross-shaped structure Gutter shaped front rail
Door type	Glazed
Number of doors	Front face: 1 door(s)
Door opening side	120 °, reversible
Lock type	3 mm double-bar lock
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Front
Removable parts	Door fixing: by hinges
Material	Lock: zamak Hinge: stainless steel Body and door: stainless steel 304L Door: Securit glass
Surface finish	Lock: chromium plated Body and door: Scotch-Brite® brushed
Thickness	1.5 mm
Product weight	5.606 kg

Okolina

standards	IEC 62208
product certifications	CAN/CSA 22 UL 508 type A
IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
environmental characteristic	Corrosive Specific hygiene

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0810 - Schneider Electric declaration of conformity	Compliant - since 0810 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
