

## NSYSM1816502DP

Kompaktno kućište Spacial SM s montažnom pločom  
– 1800 x 1600 x 500 mm



### Glavno

|                             |   |
|-----------------------------|---|
| Range                       | Spacial   |
| Product name                | Spacial SM  |
| Product or component type   | Compact enclosure   |
| Device application          | Multi-purpose   |
| Installation accessory type | Floor-standing  |
| Device composition          | 1 blocking system for left door<br>1 body<br>1 cable gland plate<br>1 mounting plate<br>1 locking system with handle for door<br>4 mounting plate bracket<br>2 door |
| Removable parts             | Door fixed by screws for hinge<br>Mounting plate bracket fixed by screws<br>Mounting plate fixed by screws for mounting plate bracket                               |
| Enclosure nominal height    | 1800 mm   |
| Enclosure nominal width     | 1600 mm   |
| Enclosure nominal depth     | 500 mm  |

### Komplementarno

|                             |  |
|-----------------------------|--|
| Number of doors             | 2 on front   |
| Door opening side           | Left 120 °<br>Right 120 °  |
| Door type                   | Plain  |
| Lock type                   | 4 points lock, handle with 5 mm double bar insert  |
| Body type                   | Single piece body with welded rear panel<br>Front part forming a rigid frame with welded corners       |
| Mounting plate description  | Plain  |
| Type of gland plate         | Standard   |
| Cable entry                 | 1 entry  |
| Material                    | Galvanised steel for mounting plate<br>Sheet steel for body<br>Sheet steel for door<br>Zamak for hinge |
| Surface finish              | Epoxy-polyester powder   |
| Colour                      | Enclosure: grey RAL 7035<br>Handle: black RAL 9005   |
| Accessibility for operation | Front  |

### Okolina

|                         |                              |
|-------------------------|------------------------------|
| standards               | IEC 62208                    |
| product certifications  | BV<br>DNV<br>UL              |
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |

### Offer Sustainability

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

|   |   |
|---|---|
| Green Premium product   | Green Premium product   |
| Compliant - since 0940 - Schneider Electric declaration of conformity | Compliant - since 0940 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold                     | Reference not containing SVHC above the threshold                     |
| Available   | Available   |
| Need no specific recycling operations                                 | Need no specific recycling operations                                 |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|