

NSYTBS16128T

Kutija ABS IP66 IK07 RAL7035 Unut.V150 Š105 D80
Vanj.V164 Š121 D87,proz.pok.H20



Glavno

| | |
|---------------------------|---|
| Range | Thalassa |
| Product name | Thalassa TBS |
| Device application | Multi-purpose |
| Product or component type | Industrial box |
| Height | 164 mm |
| Width | 121 mm |
| Depth | 87 mm |
| Internal height | 150 mm |
| Internal width | 105 mm |
| Internal depth | 80 mm |
| Enclosure mounting | Wall mounted |
| Device composition | 1 x body 1 x cover 4 x cover screw |
| Quantity per set | Set of 2 |
| Body type | One piece moulded |
| Type of front cover | Low transparent cover |
| Cover fixing | Plastic screws |
| Lock type | Outside sealed area: flat screwdriver captive screw |
| Removable parts | Cover, by captive screws |

Komplementarno

| | |
|---------------------------------------|---------------------------------------|
| Material | ABS (acrylonitrile butadiene-styrene) |
| Colour | Grey (RAL 7035) Transparent |
| Standards | IEC 62208 |
| Product certifications | DEMKO SEMKO TÜV |
| Electrical insulation class | Class II |
| IP degree of protection | IP66 conforming to NEMA 4.4X |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Fire resistance | 650 °C conforming to IEC 60695-2-11 |
| Ambient air temperature for storage | -15...40 °C |
| Ambient air temperature for operation | -25...60 °C |
| Product weight | 0.34 kg |

Okolina

Offer Sustainability

| | |
|--|---|
| Green Premium product | Green Premium product |
| Compliant - since 0940 - Schneider Electric declaration of conformity | Compliant - since 0940 - Schneider Electric declaration of conformity |
| Reference contains SVHC above the threshold - go to CaP for more details | Reference contains SVHC above the threshold |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poipunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Available

Available

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
