



Glavno

Range of product	Sedna
Range	Sedna
Device application	Control
Product or component type	Switch
Switch function	Double 2-way
Device presentation	Without frame
Rated current	10 AX - 250 V AC
Cover plate colour tint	Aluminium
Connections - terminals	Screwless terminals

Komplementarno

Accessory / separate part type	Claw and screw for mechanism
Power range	2300 W
Wiring device mounting	Flush
Number of cables	2 x 2.5 mm ²
Cable stiffness	Flexible Rigid
Wire stripping length	13 mm
Material	Thermoplastic ABS-UV stabilised
Surface finish	Glossy
Fixing mode	Screws Screws Claws, span of claws working range : 51...70 mm
Height	71 mm
Width	71 mm
Depth	37 mm
Projecting depth	12 mm
Product weight	0.08651 kg

Okolina

standards	IEC 60669-1
quality labels	CE
product certifications	GOST-R
IP degree of protection	IP20

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1715 - Schneider Electric declaration of conformity	Compliant - since 1715 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
 Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

