



Glavno

| | |
|---------------------------|--------------------|
| Range of product | Sedna |
| Product or component type | Push-button dimmer |
| Switch function | 2-way |
| Device presentation | Without frame |
| Cover plate colour tint | White |
| Connections - terminals | Pillar terminals |

Komplementarno

| | |
|--------------------------------|--|
| Wiring device mounting | Flush |
| Dimmer application | Inductive load Resistive load |
| Load type | 230 V AC halogen lamp 60...500 W 230 V AC incandescent lamp 60...500 W Low voltage halogen lamp with ferromagnetic transformer 60...500 VA |
| [Ue] rated operational voltage | 230 V AC |
| Protection type | Fuse protection |
| Fuse type | F2.5AH/250 V |
| Number of cables | 1 x 2.5 mm ² |
| Cable stiffness | Flexible Rigid |
| Wire stripping length | 7 mm |
| Material | Thermoplastic ABS-UV stabilised |
| Surface finish | Glossy |
| Fixing mode | Screws Claws, span of claws working range: 51...80 mm |
| Height | 71 mm |
| Width | 71 mm |
| Depth | 47.5 mm |
| Projecting depth | 20 mm |
| Product weight | 0.13574 kg |

Okolina

| | |
|-------------------------|--------------|
| standards | EN 60669-2-1 |
| quality labels | CE |
| product certifications | GOST-R |
| IP degree of protection | IP20 |

Offer Sustainability

| | |
|---|---|
| Not Green Premium product | Not Green Premium product |
| Compliant - since 0946 - Schneider Electric declaration of conformity | Compliant - since 0946 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Need no specific recycling operations | Need no specific recycling operations |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
 Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
