



Glavno

Range of product	Sedna
Product or component type	Socket-outlet
Device presentation	Complete product
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Rated current	16 A - 250 V AC
Cover plate colour tint	Aluminium
Connections - terminals	Lift terminals

Komplementarno

Wiring device mounting	Flush
Power range	3680 W
Number of cables	2 x 2.5 mm ²
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13 mm
Material	ASA + PC
Surface finish	Glossy
Fixing mode	Screws Screws Claws, span of claws working range : 52...69 mm
Height	120 mm
Width	84 mm
Depth	48 mm
Projecting depth	23.3 mm
Product weight	0.1031 kg

Okolina

standards	IEC 60884-1
IP degree of protection	IP20

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1715 - Schneider Electric declaration of conformity	Compliant - since 1715 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
 Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.