


## XB4BVB4

crvena potpuna signalna žaruljica Ø 22 obična leća s ugrađenim LED-om 24 V



### Glavno

|                                 |                       |
|---------------------------------|-----------------------|
| Range of product                | Harmony XB4           |
| Product or component type       | Complete pilot light  |
| Device short name               | XB4                   |
| Bezel material                  | Chromium plated metal |
| Fixing collar material          | Zamak                 |
| Mounting diameter               | 22 mm                 |
| Head type                       | Standard              |
| Sale per indivisible quantity   | 1                     |
| Shape of signaling unit head    | Round                 |
| Cap/operator or lens colour     | Red                   |
| Operator additional information | With plain lens       |
| Light source                    | Protected LED         |
| Bulb base                       | Integral LED          |
| Light source colour             | Red                   |
| [Us] rated supply voltage       | 24 V AC/DC, 50/60 Hz  |

### Komplementarno

|                                        |                                                                                                                                                                                                           |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Height                                 | 47 mm                                                                                                                                                                                                     |
| Width                                  | 30 mm                                                                                                                                                                                                     |
| Depth                                  | 54 mm                                                                                                                                                                                                     |
| Terminals description ISO n°1          | (X1-X2)PL                                                                                                                                                                                                 |
| Product weight                         | 0.08 kg                                                                                                                                                                                                   |
| Resistance to high pressure washer     | 7000000 Pa at 55 °C, distance: 0.1 m                                                                                                                                                                      |
| Connections - terminals                | Screw clamp terminals: <= 2 x 1.5 mm <sup>2</sup> with cable end conforming to EN/IEC 60947-1<br>Screw clamp terminals: 1 x 0.22...2 x 2.5 mm <sup>2</sup> without cable end conforming to EN/IEC 60947-1 |
| [Ui] rated insulation voltage          | 250 V (degree of pollution: 3) conforming to EN 60947-1                                                                                                                                                   |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to EN 60947-1                                                                                                                                                                             |
| Signalling type                        | Steady                                                                                                                                                                                                    |
| Supply voltage limits                  | 19.2...30 V DC<br>21.6...26.4 V AC                                                                                                                                                                        |
| Current consumption                    | 18 mA                                                                                                                                                                                                     |
| Service life                           | 100000 h at rated voltage and 25 °C                                                                                                                                                                       |
| Surge withstand                        | 1 kV conforming to IEC 61000-4-5                                                                                                                                                                          |

### Okolina

|                                       |                                                       |
|---------------------------------------|-------------------------------------------------------|
| protective treatment                  | TH                                                    |
| ambient air temperature for storage   | -40...70 °C                                           |
| ambient air temperature for operation | -40...70 °C                                           |
| electrical shock protection class     | Class I conforming to IEC 60536                       |
| IP degree of protection               | IP67<br>IP66 conforming to IEC 60529<br>IP69K<br>IP69 |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                    |
| IK degree of protection               | IK06 conforming to IEC 50102                          |


Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

|                                       |                                                                                                                                                                                |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5<br>JIS C 4520<br>UL 508<br>CSA C22.2 No 14                                                          |
| product certifications                | CSA<br>UL listed                                                                                                                                                               |
| vibration resistance                  | 5 gn (f = 12...500 Hz) conforming to IEC 60068-2-6                                                                                                                             |
| shock resistance                      | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |
| resistance to fast transients         | 2 kV conforming to IEC 61000-4-4                                                                                                                                               |
| resistance to electromagnetic fields  | 10 V/m conforming to IEC 61000-4-3                                                                                                                                             |
| resistance to electrostatic discharge | 6 kV on contact (on metal parts) conforming to IEC 61000-4-2<br>8 kV in free air (in insulating parts) conforming to IEC 61000-4-2                                             |
| electromagnetic emission              | Class B conforming to IEC 55011                                                                                                                                                |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

### Dimensions



e : clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.

b : 30 mm / 1.18 in.

c : 46.5 mm / 1.83 in.

### Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

| Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board                                                                                                                                                                                                                                                                                     | Connection by Faston Connectors |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
|                                                                                                                                                                                                                                                                                                                                                                           |                                 |
| <p>(1) Diameter on finished panel or support</p> <p>(2) 40 mm min. / 1.57 in. min.</p> <p>(3) 30 mm min. / 1.18 in. min.</p> <p>(4) <math>\varnothing</math> 22.5 mm / 0.89 in. recommended (<math>\varnothing</math> 22.3 mm <math>^{+0.4}_0</math> / 0.88 in. <math>^{+0.016}_0</math>)</p> <p>(5) 45 mm min. / 1.78 in. min.</p> <p>(6) 32 mm min. / 1.26 in. min.</p> |                                 |