

## XD2CF1111

potpuni kontroler s upravljačkom palicom – Ø 30 – 4  
smjera – 1 C/O po smjeru

### Glavno

|                           |                              |
|---------------------------|------------------------------|
| Range of product          | Harmony XD2                  |
| Product or component type | Complete joystick controller |
| Device short name         | XD2                          |
| Mounting diameter         | 30 mm                        |
| Bezel material            | Chromium plated metal        |

### Komplementarno

|                                |   |
|--------------------------------|---|
| Operator position information  | All positions   |
| Notch per direction            | 1   |
| Operator direction information | 4 directions  |
| Contacts type and composition  | 1 C/O snap action   |
| Short-circuit protection       | 10 A gG (gl) Neozed cartridge fuse conforming to EN/IEC 60947-5-1   |
| Connections - terminals        | Captive screw clamp terminals - 2 x 1.5 mm <sup>2</sup> with or without cable end<br>Captive screw clamp terminals - 1 x 2.5 mm <sup>2</sup> with or without cable end  |
| Electrical durability          | 1000000 cycles at 230 V AC-15, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles at 127 V AC-15, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles at 24 V DC-13, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles at 48 V DC-13, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles at 120 V DC-13, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles at 48 V AC-15, operating rate: 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C |
| Contact code designation       | A600-Q600   |
| Overvoltage category           | Class I conforming to IEC 61140   |
| Mechanical durability          | 1000000 cycles  |
| Fixing center                  | 100 x 100 mm  |
| Return                         | To 0 position   |
| Height                         | 190 mm  |
| Depth                          | 91 mm   |
| Product weight                 | 0.39 kg   |

### Okolina

|                                       |   |
|---------------------------------------|---|
| standards                             | EN/IEC 60947-5-1                                    |
| product certifications                | CSA<br>DEMKO<br>GL                                  |
| protective treatment                  | TC  |
| ambient air temperature for storage   | -40...70 °C   |
| ambient air temperature for operation | -25...70 °C   |
| vibration resistance                  | 25 gn (f = 10...500 Hz) conforming to IEC 60068-2-6 |
| shock resistance                      | 50 gn conforming to IEC 60068-2-27                  |
| IP degree of protection               | IP65 conforming to IEC 60529                        |

Informacije dane u ovoj dokumentaciji sadrže opće i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.