


XESD2241

kontaktni blok s opružnim povratom - 3 NO+1 NO-
mont.s pred.str.,središta od 40mm



Glavno

| | |
|-------------------------------|------------------------------|
| Range of product | Harmony XAC |
| Product or component type | Contact block |
| Component name | XESD |
| Electrical circuit type | Power circuit |
| Contact block application | Single speed |
| Contact block type | Double |
| Type of operator | 2 spring return |
| Product compatibility | XACB |
| Mechanical interlocking | With mechanical interlocking |
| Contacts type and composition | 3 NO + 1 NO |
| Poles description | 3-pole |
| Mounting of block | Front mounting |
| Contact operation | Simultaneous Snap action |

Komplementarno

| | |
|--|--|
| Connections - terminals | Screw clamp terminals, connection capacity: 1 x 2.5 mm ² with or without cable end Screw clamp terminals, connection capacity: 2 x 1.5 mm ² with or without cable end |
| Horizontal fixing centres | 40 mm |
| Mechanical durability | 1000000 cycles |
| [I _{th}] conventional enclosed thermal current | 20 A |
| [U _i] rated insulation voltage | 300 V conforming to CSA |
| [U _{imp}] rated impulse withstand voltage | 6 kV conforming to IEC 60947-1 |
| Operating force | 32 N |
| Short-circuit protection | <= 12 A fuse protection by cartridge fuse type aM |
| Rated operational power in W | 3000 W AC-3 at 240 V 3000 W AC-4 at 400 V |
| Rated power in hp | 3 hp at 240 V |
| Electrical durability | 1000000 cycles AC-3, 3000 W at 400 V, operating rate = 10 cyc/mn, load factor = 0.4 conforming to IEC 60947-3 appendix A 1000000 cycles AC-4, 3000 W at 400 V, operating rate = 10 cyc/mn, load factor = 0.4 conforming to IEC 60947-3 appendix A 700000 cycles AC-3, 3000 W at 240 V, operating rate = 10 cyc/mn, load factor = 0.4 conforming to IEC 60947-3 appendix A 700000 cycles AC-4, 3000 W at 240 V, operating rate = 10 cyc/mn, load factor = 0.4 conforming to IEC 60947-3 appendix A |
| Terminals description ISO n°1 | (13-14)NO (23-24)NO (33-34)NO (43-44)NO B |
| Terminals description ISO n°2 | (44-84)NO (53-54)NO (63-64)NO (73-74)NO B |
| Terminal identifier | (11-12)NC (13-14)NO |
| Product weight | 0.21 kg |

Okolina

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

| | |
|---------------------------------------|---|
| standards | EN 60947-3 IEC 60947-3 CSA C22.2 No 14 |
| ambient air temperature for operation | -25...70 °C |
| ambient air temperature for storage | -40...70 °C |
| vibration resistance | 15 gn (f = 10...500 Hz) conforming to IEC 60068-2-6 |
| shock resistance | 100 gn conforming to IEC 60068-2-27 |
| electrical shock protection class | Class II conforming to IEC 61140 |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|