

## XKDZ1508

potenciometar – 800 oma – 15 mm – za XKD/XKM



### Glavno

Product or component type	Controllers separate parts
Accessory / separate part category	Control accessories
Product specific application	Heavy hoisting applications Medium hoisting applications
Product compatibility	XKD XKM
Accessory / separate part type	Potentiometer
Condition of use	For applications requiring an extended neutral zone
Ohmic value	800 Ohm
Size	15 mm

### Komplementarno

Standards	UTE 93-265
Potentiometer characteristic	Continuous rotational operation Linear function
Operating angle	360 °
Mechanical durability	3000000 cycles
Centre tap	Wired out to terminal
Centre tap dead zone	30 °
Power dissipation in W	3 W 85 °C
Connections - terminals	Flying leads from soldered standard tags
Product weight	0.055 kg

### Okolina

mounting mode	By the body
---------------	-------------

### Contractual warranty

Warranty period	18 months
-----------------	-----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.